

40m Aluminium Crew/Utility Boat



VESSEL :

Vessel: 40m Aluminium Crew/Utility Boat
 Classification: ABS+A1 HSC Crewboat +AMS
 Safety Regulation: ABS and Flag state requirements
 Outline of Vessel: All welded aluminum Monohull with quadruple propellers/twin rudders.
 Forward fully air conditioning crew accommodation/passenger saloon.
 And flush,no-obstructed cargo deck

ACCOMMODATIONS :

Passenger Capacity: 100 Aircraft type economy class seat
 Crew 10 bunks in 5 cabins
 Mess Seating for 10 Crew

MAIN PARTICULARS :

Length Overall : 40.00m
 Beam : 8.20m
 Moulded depth : 3.65m
 Moulded draft (Approx) : 2.0m
 Summer Freeboard : 1.65m

ELECTRONICS AND CONTROLS :

GMDSS GMDSS A2
 VHF Furuno FM-8900S + 2 hand held
 SSB Radio Furuno FS-1575 + I-COM IC-M710 (non GMDSS)
 Satellite communication/Fax INMARSAT FLEETBROADBAND FELCOM-250
 GPS Furuno GP-170
 Depth / Echo Sounder 1 unit depth-Furuno FE-800
 Gyro Compass ANSCHUTZ STD-22
 Magnetic Compass 6" Magnetic Compass (with deviation card)
 Autopilot system ANSCHUTZ NP-60
 Navtex Furuno NX700B
 Marine Radar 2 unit Furuno FAR2117
 EPIRB ACR RLB-38
 SART ACR PATHFINER3
 AIS Furuno FA-150
 Public Address / Intercom System Vingtor Pro-700
 Search Lights 3 units KARLDOSE, 1000W
 Chart Plotter GARMIN GPSMAP5012

CARGO DECK :

Clear Deck Space 115 m² (18.0m length x 6.4 m width)
 Safe Deck Loading 85 tonnes
 Deck Strength 2.5t/m2
 Deck Crane 1Ton@6m
 Remark : Adequate cargo retainers and lashing lugs
 on both sides for securing deck cargo
 Aft Deck suitable for helicopter winching

TONNAGE :

GRT (Approx.) 292
 NRT (Approx.) 88
 Deadweight(Approx.) 190 MT

TANK CAPACITIES:

Fuel Oil @ 23 cu.m/hr discharge rate 100,000 litres
 Fresh Water 30,000 litres

MACHINERY :

Number of Main Engines 4
 Propulsion Quadruple Screw
 Make Type Cummins KTA 38-M2
 Total BHP / KW 4 x 1350 hp
 Propellers 4 Fixed Pitch
 Bow Thruster 1 x 90kw

OIL POLLUTION TANK CAPACITY AND CONTROL :

Dirty Oil Tank 1.0 cub m
 Oily water separator 0.25 cu./hr
 Sewage Treatment plant Hamworthy KSE STC01 Super trident sewage plant

PERFORMANCE

Service Speed 27 knots, 85% MCR @ 50 MT DWT
 Maximum Fuel Consumption 1006 L/hr
 Laden Speed 18 knots @ 85% MCR Fully Loaded

LIFE SAVING (SOLAS) EQUIPMENT :

Life Rafts Three 50 pax SOLAS type on each side
 Life Jackets 120
 Life Buoys 8 on board per SOLAS
 Rescue Zone Yes
 Scrambling Nets 2 units
 Other Equipment Pyrotechnics, Line throwing apparatus

GENERATING SETS (AUXILIARIES) :

Prime Movers 2 x 91KW @ 1500 RPM
 Make / Type Cummins 6BT5.9-DM or equal
 Generators SIMENS 1FC2224-4, 2 x 80kw
 Vessel Power Supply 415/240 Volt AC, 50Hz, 3ph + 24 Volt DC

EMERGENCY RESPONSE FEATURES :

Fire Fighting(Optional) 600 m³/hr monitor
 Inflatable Workboat with 25HP outboard motor Provided